

View Online at <https://aerobasegroup.com/nsn/5935-01-116-5492>

Body Style:

Straight shape

Overall Length:

1.080 inches

Overall Height:

18.385 inches

Overall Width:

0.208 inches

Environmental Protection:

Corrosion resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.089 inches and 0.094 inches

Distance Between Mounting Facility Centers:

0.865 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

21 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Copper single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 2nd treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Shell Material:

Steel comp 304

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Mil-f-14072, e-300 military specification single treatment response

Shell Material Specification:

Qq-s-766 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg military specification single material response single mating end

Included Contact Quantity:

21 single mating end single contact grouping

Included Contact Type:

Twisted pin single mating end single contact grouping

Special Features:

Insulation color white, no. 26 wire size

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.021 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.