

View Online at <https://aerobasegroup.com/nsn/5935-01-116-7448>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Overall Diameter:**

0.515 inches

**Environmental Protection:**

Vibration resistant and shock resistant and moisture resistant and corrosion resistant

**Cable Entrance Diameter:**

0.230 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Ahab 10-7 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Nickel

**Included Contact Quantity:**

7 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.007 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0