Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-116-7454

Body Style:

Straight type

Overall Length:

4.900 inches

Overall Height:

0.677 inches

Overall Width:

0.400 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

4.650 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single

material response single mating end single contact grouping

NSN 5935-01-116-7454

Electrical Receptacle Connector - Page 2 of 2



Guide Design And Location:
D shape pin left-hand at 9 oclock and d shape socket right-hand at 9 oclock
Insert Material Specification:
Mil-m-14, ty gdi-30 or ty sdg-f military specification single material response single mating end
Included Contact Quantity:
122 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.122 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.