NSN 5935-01-117-0542

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-117-0542 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.031 inches **Overall Diameter:** 0.750 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Distance From Mounting Shoulder To Front Face:** 0.134 inches **Mounting Facility Thickness:** 0.094 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 6-aug single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 550.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:**

Externally threaded coupling ring

Thready Qty Per Inch (tpi):

18 and 20

Thread Size:

0.562 inches and 0.750 inches

NSN 5935-01-117-0542

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
6 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.006 gold grains, troy and 0.006 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0