

View Online at <https://aerobasegroup.com/nsn/5935-01-117-2208>

**Body Style:**

Straight shape spring mount

**Overall Length:**

1.641 inches

**Overall Diameter:**

Between 1.235 inches and 1.265 inches

**Environmental Protection:**

Thermal shock resistant and corrosion resistant and vibration resistant and moisture resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

36861 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Snap ring

**Operating Temperature Rating:**

Between -67.0 degrees fahrenheit and 392.0 degrees fahrenheit

**Features Provided:**

Safety wire hole

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Crimping Tool Identifying Number:**

1113-91-550-0127

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum

**Included Contact Quantity:**

12 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round keyed

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.012 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.