

View Online at <https://aerobasegroup.com/nsn/5935-01-117-2208>

Body Style:

Straight shape spring mount

Overall Length:

1.641 inches

Overall Diameter:

Between 1.235 inches and 1.265 inches

Environmental Protection:

Thermal shock resistant and corrosion resistant and vibration resistant and moisture resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

36861 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Snap ring

Operating Temperature Rating:

Between -67.0 degrees fahrenheit and 392.0 degrees fahrenheit

Features Provided:

Safety wire hole

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Crimping Tool Identifying Number:

1113-91-550-0127

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Included Contact Quantity:

12 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round keyed

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.