NSN 5935-01-118-0330

Straight shape, external coupling w/backshell

Thread Class: 2a and 2a

Body Style:

Overall Length: 2.125 inches

Overall Diameter:

2.224 inches

Thread Direction:

Right-hand and right-hand

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-118-0330

Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
32-7 single mating end
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
2.000 inches and 2.000 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Silicon single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end all contact groupings

NSN 5935-01-118-0330Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
7 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.064 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns and uns
Specification Data:
96906-ms3451 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.