## NSN 5935-01-118-1515

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-118-1515

**Body Style:** 

Flush flange mounting

**Bushing Diameter:** 

1.718 inches

**Overall Diameter:** 

2.562 inches

**Unthreaded Mounting Hole Diameter:** 

0.156 inches

**Distance From Mounting Shoulder To Rear Face:** 

1.718 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

3 single mating end

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

15.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:** 

125.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:** 

125.0 single mating end all contact groupings

Shell Type:

Solid

**Connector Locking Method:** 

Contact twistlock

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Insert Material:** 

Plastic polyamide single mating end

**Terminal Type:** 

Screw single mating end all contact groupings

**Included Contact Quantity:** 

2 single mating end 2nd contact grouping

**Included Contact Type:** 

Curved socket w/inside lip single mating end 1st contact grouping

**Special Features:** 

Two mtg holes spaced 2.187 in. C to c

Shelf Life:

N/a

## NSN 5935-01-118-1515

Electrical Receptacle Connector - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A039b0