NSN 5935-01-118-7446

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-118-7446

Thread Direction: Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 32.0 millimeters **Overall Height:** Between 43.3 millimeters and 43.4 millimeters **Overall Width:** Between 43.3 millimeters and 43.4 millimeters **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** Between 3.6 millimeters and 4.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 34.92 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 34.92 millimeters **Distance From Mounting Shoulder To Front Face:** Between 19.2 millimeters and 20.8 millimeters **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** Axba 23-21 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Spring friction **Thread Size:** 34.0 millimeters **Thread Pitch In Millimeters:** 1.00

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-118-7446

Electrical Receptacle Connector - Page 2 of 2



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold and silver single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Thread Tolerance Class:** 6h external **Included Contact Quantity:** 21 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.021 gold grains, troy and 0.021 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Iso s **Specification Data:** 81349-mil-dtl-38999/40 government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A039b0