

View Online at <https://aerobasegroup.com/nsn/5935-01-119-4417>

Body Style:

Right angle type

Overall Length:

1.550 inches

Overall Height:

0.550 inches

Overall Width:

0.359 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

1.300 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape socket left-hand top at 6 oclock and d shape pin right-hand bottom at 6 oclock

Insert Material Specification:

Mil-m-14 military specification single material response single mating end or mil-p-19833 military specification single material response single mating end

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/57 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.