Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-119-7454

Body Style:

Straight edge type w/card guide

Overall Length:

1.662 inches

Overall Width:

0.400 inches

Body Height:

0.745 inches

Environmental Protection:

Shock resistant and vibration resistant and humidity resistant

Board Accommodated Length:

1.538 inches single board

Board Accommodated Width:

Between 0.055 inches and 0.070 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Inter-contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping and tin single mating end single contact

grouping

Insert Material:

Plastic polyamide single mating end and glass single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

