

View Online at <https://aerobasegroup.com/nsn/5935-01-120-0906>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.370 inches

Overall Diameter:

Between 0.461 inches and 0.481 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof

Distance From Mounting Shoulder To Front Face:

0.589 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

14-7 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

101.0 and 168.0 and 211.0 and 342.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

20

Thread Size:

1.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Metal ferrous single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Tin

Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.007 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-83723/65 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.