Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-120-4413

Body Style:

Straight shape, external coupling

Overall Length:

0.870 inches

Overall Height:

1.047 inches

Overall Width:

1.047 inches

Environmental Protection:

Thermal shock resistant and moisture resistant

Unthreaded Mounting Hole Diameter:

0.128 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

Distance From Mounting Shoulder To Front Face:

Between 0.055 inches and 0.056 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Nickel alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd

treatment response single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: | |
|--------------------|---|
| Tab, solder lug s | single mating end single contact grouping |
| Contact Material | I Specification: |
| Mil-i-23011 milita | ry specification single material response single mating end single contact grouping |
| Shell Material: | |
| Steel | |
| Shell Surface Tr | reatment: |
| Tin and copper | |
| Shell Surface Tr | reatment Specification: |
| Mil-t-10727, type | a 1 military specification 1st treatment response and mil-c-14550, cl 3 military specification 2nd treatment response |
| Shell Material S | pecification: |
| Qq-s-637 federal | specification single material response |
| Included Contac | ct Quantity: |
| 6 single mating e | nd single contact grouping |
| Included Contac | ct Type: |
| Round pin single | mating end single contact grouping |
| Precious Materia | al And Location: |
| Contact surfaces | gold |
| Precious Materia | al And Weight: |
| 0.030 gold grains | s, troy |
| Precious Materia | al: |
| Gold | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure | x: |
| | |
| Demilitarization | : |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (military | Standard): |
| Mil-i-23011 spec. | |