## NSN 5935-01-120-7008

Round pin single mating end single contact grouping

**Body Style:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-120-7008

Straight type
Overall Length:
2.050 inches
Overall Height:
0.625 inches
Overall Width:
0.250 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.800 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder stud single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14, gdi-30f or sdg-f military specification single material response single mating end
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:

## NSN 5935-01-120-7008

Electrical Receptacle Connector - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

Mil-std (military Standard):

Shelf Life:

Mil-g-45204 spec.