Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-121-0413



**Thread Class:** 

2a

**Thread Direction:** 

Right-hand

## **Body Style:**

Straight shape w/screw locks

**Overall Length:** 

1.185 inches

**Overall Height:** 

0.500 inches

**Overall Width:** 

0.305 inches

**Environmental Protection:** 

Vibration resistant and shock resistant and salt water resistant

#### Threaded Device Type:

Coupling facility

Mating End Quantity:

1

**Contact Position Arrangement Style:** 

25 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

# Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

# Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

Shell Type:

Solid

**Connector Locking Method:** 

Jackscrew

Thready Qty Per Inch (tpi):

56

**Thread Size:** 

0.086 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# NSN 5935-01-121-0413

Electrical Plug Connector - Page 2 of 2



**Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Wire wrap single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 25 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.025 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0