Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-121-1744

Body Style:

- Straight type
- **Overall Length:**
- 3.093 inches

Overall Width:

- 0.330 inches
- **Body Height:**
- 0.408 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1800.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

36 single mating end single contact grouping

Included Contact Type:

Bifurcated accordian leaf spring single mating end single contact grouping

Special Features:

Single board length 3.093 and board thickness 0.062

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.036 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2



Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.