

View Online at <https://aerobasegroup.com/nsn/5935-01-121-2284>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/cable clamp

Overall Length:

1.593 inches

Bushing Diameter:

0.750 inches

Overall Height:

Between 0.985 inches and 1.000 inches

Overall Width:

Between 0.985 inches and 1.000 inches

Environmental Protection:

Corrosion resistant and vibration resistant and shock resistant and moisture resistant

Unthreaded Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.713 inches and 0.723 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.713 inches and 0.723 inches

Distance From Mounting Shoulder To Front Face:

Between 0.641 inches and 0.671 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-39012/02 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.