NSN 5935-01-121-6300

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-121-6300 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.217 inches and 1.223 inches **Overall Height:** 1.312 inches **Overall Width:** 1.312 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** Between 0.627 inches and 0.632 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 550.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 77.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin

Thread Size: 1.063 inches

NSN 5935-01-121-6300

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Nickel and cadmium
Included Contact Quantity:
66 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0