Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-121-9420

| Thread Class: |
|---|
| 2b |
| Thread Direction: |
| Right-hand |
| |
| Body Style: |
| Straight shape, rectangular |
| Overall Length: 1.098 inches |
| Overall Height: |
| 0.944 inches |
| Overall Width: |
| 0.944 inches |
| |
| Center To Center Distance Between Mounting Facilities Parallel To Height: 0.719 inches |
| |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.719 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 Control Desition American (Chiles |
| Contact Position Arrangement Style: |
| 30 number 22 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Polarization Method: |
| Polarization boss |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Screw |
| Thready Qty Per Inch (tpi): |
| 48 Thread Size |
| Thread Size: |
| |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and copper single mating end single contact grouping |

NSN 5935-01-121-9420

Electrical Receptacle Connector - Page 2 of 2



| Plas | stic diallyl phthalate single mating end |
|------|---|
| Cor | ntact Surface Treatment Specification: |
| Mil- | g-45204 military specification 1st treatment response single mating end single contact groupir |
| Ter | minal Type: |
| Crir | mp single mating end single contact grouping |
| Cor | ntact Material Specification: |
| Qq- | -c-530a federal specification single material response single mating end single contact groupir |
| She | ell Material: |
| Stai | inless steel |
| She | ell Material Specification: |
| Qq- | -s-766, type 302 federal specification single material response |
| Inse | ert Material Specification: |
| Mil- | m-14, type sdg-f military specification single material response single mating end |
| Incl | Iuded Contact Quantity: |
| 30 s | single mating end single contact grouping |
| Incl | luded Contact Type: |
| Rou | und socket single mating end single contact grouping |
| Pre | cious Material And Location: |
| Cor | ntact surfaces gold |
| Pre | cious Material And Weight: |
| 0.03 | 30 gold grains, troy |
| Pre | cious Material: |
| Gol | d |
| Thr | read Series Designator: |
| Unc | |
| She | elf Life: |
| N/a | |
| Uni | it Of Measure: |
| | |
| Der | militarization: |
| No | |
| Fiig | j: |
| A03 | 39b0 |
| Mil- | -std (military Standard): |
| Mil- | -g-45204 spec. |