

View Online at <https://aerobasegroup.com/nsn/5935-01-121-9423>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, rectangular

Overall Length:

1.430 inches

Overall Height:

1.860 inches

Overall Width:

2.875 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.149 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.500 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

158 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Polarization boss

Connector Locking Method:

Jackscrew

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

158 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.158 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Specification Data:

81349-mil-c-28748/09 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.