NSN 5935-01-122-2482

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-122-2482

Body Style: Pcb, external coupling **Overall Length:** 0.548 inches **Overall Height:** 0.375 inches **Overall Width:** 0.375 inches **Environmental Protection:** Corrosion resistant and vibration resistant and shock resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 0.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.250 inches **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic fluorocarbon single mating end **Contact Surface Treatment Specification:** Mil-g-45204b military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Gold

Insert Material Specification:

L-p-403 federal specification single material response single mating end

NSN 5935-01-122-2482

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and shell surface gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204b spec.