

View Online at <https://aerobasegroup.com/nsn/5935-01-122-4748>

Thread Class:

2b and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.660 inches

Overall Diameter:

0.812 inches

Mounting Facility Thickness:

0.150 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma 2nd mating end

Contact Removability:

Removable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring and externally threaded shell

Thready Qty Per Inch (tpi):

24 and 32 and 36

Thread Size:

0.625 inches and 0.375 inches and 0.250 inches

Contact Material:

Tellurium all mating ends single contact grouping and copper all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Included Contact Quantity:

1 2nd mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces and body surfaces gold and mounting nut surface silver

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef and unef and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0