

View Online at <https://aerobasegroup.com/nsn/5935-01-122-6639>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

5.135 inches

**Overall Height:**

0.610 inches

**Overall Width:**

0.370 inches

**Distance Between Mounting Facility Centers:**

4.875 inches

**Board Accommodated Length:**

4.400 inches single board

**Threaded Device Type:**

Mounting stud

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

600.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic phenolic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

86 single mating end single contact grouping

**Included Contact Type:**

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.086 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.