NSN 5935-01-122-7587

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-122-7587 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.130 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.684 inches and 1.692 inches **Overall Height:** Between 1.123 inches and 1.171 inches **Overall Width:** 0.880 inches **Environmental Protection:** Corrosion resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.463 inches and 0.473 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 34 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 4100.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket and shell Shell Type: Solid Thready Qty Per Inch (tpi): **Thread Size:** 0.112 inches **Terminal Location:**

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-122-7587

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 1, grade c military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Shell Guide Type And Location Designator:
B pin
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
34 single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.034 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):