# NSN 5935-01-122-8031

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-122-8031

**Thread Class:** 

2a and 2b and 2a

**Thread Direction:** 

Right-hand and right-hand and right-hand

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.307 inches and 2.317 inches

**Overall Height:** 

Between 0.796 inches and 0.828 inches

**Overall Width:** 

Between 0.745 inches and 0.755 inches

**Environmental Protection:** 

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:** 

Between 1.996 inches and 2.004 inches

**Threaded Device Type:** 

Coupling facility and mounting stud

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

42 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Jackscrew

**Connector Locking Method:** 

Jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 32 and 40

**Thread Size:** 

0.138 inches and 0.138 inches and 0.112 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

# NSN 5935-01-122-8031

Electrical Receptacle Connector - Page 2 of 2



# **Terminal Type:**

Crimp single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material responses single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

42 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Jackscrew type-female and location-left handandjackscrew type-male and location-right hand

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.042 gold grains, troy

#### **Precious Material:**

Gold

# **Thread Series Designator:**

Unc and unc and unc

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# Demilitarization:

No

# Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.