## NSN 5935-01-122-9092

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-122-9092 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.781 inches **Overall Height:** 0.578 inches **Overall Width:** 0.281 inches **Distance Between Mounting Facility Centers:** 0.531 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 11 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-01-122-9092

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification
-------------------------------

Mil-m-14, sdg-f military specification single material response single mating end

**Unable To Decode:** 

Unable to decode and unable to decode

**Included Contact Quantity:** 

11 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.011 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.