

View Online at <https://aerobasegroup.com/nsn/5935-01-123-0688>

Body Style:

Right angle type

Overall Length:

2.310 inches

Overall Width:

0.252 inches

Environmental Protection:

Humidity resistant and moisture proof and shock proof

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

170.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

170.0 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 cl 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14 ty sdg-f or gd1-30f military specification single material response single mating end

Included Contact Quantity:

33 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.033 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.