## NSN 5935-01-123-1928

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-1928 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.812 inches **Overall Diameter:** 1.620 inches **Environmental Protection:** Humidity resistant and heat resistant and cold resistant **Distance From Mounting Shoulder To Front Face:** 0.688 inches **Mounting Facility Thickness:** 0.040 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Err-090 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** Test set, mk 46 torpedo **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Iron alloy single mating end single contact grouping and nickel alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Cadmium single mating end single contact grouping

## NSN 5935-01-123-1928

A039b0

Mil-i-23011 spec.

Mil-std (military Standard):

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Qq-p-416, class 1, type 2 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Mil-i-23011, class 1 military specification single material response single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, class 1, type 2 federal specification single treatment response
Included Contact Quantity:
14 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: