Electrical Plug Connector - Page 1 of 2

<u>AeroBase</u> Groun

View Online at https://aerobasegroup.com/nsn/5935-01-123-3724

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
0.625 inches
Overall Diameter:
1.156 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
14-37 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thread Length:
0.219 inches
Thready Qty Per Inch (tpi):
20
Thread Size:
0.812 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crime single meting and single contest grouping

Crimp single mating end single contact grouping

NSN 5935-01-123-3724

Electrical Plug Connector - Page 2 of 2



Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.037 gold grains, troy and 0.037 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data: 96906-ms27336 government standard Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-c-27599 spec.