NSN 5935-01-123-5261

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-5261 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 0.803 inches **Overall Height:** 1.420 inches **Overall Width:** 2.687 inches **Environmental Protection:** Humidity resistant **Unthreaded Mounting Hole Diameter:** 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.875 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.375 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 8.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 2000.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Screw

Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.190 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

NSN 5935-01-123-5261

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape socket left-hand at 5 oclock and d shape socket right-hand at 5 oclock

Insert Material Specification:

Mil-m-14f, ty sdgf military specification single material response single mating end

Included Contact Quantity:

120 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.120 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.