

View Online at <https://aerobasegroup.com/nsn/5935-01-123-5264>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, rectangular

Overall Length:

0.803 inches

Overall Height:

0.875 inches

Overall Width:

2.592 inches

Environmental Protection:

Moisture resistant

Unthreaded Mounting Hole Diameter:

0.136 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.468 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.280 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

8.5 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

40

Thread Size:

0.125 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape socket right-hand at 5 oclock

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

56 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.056 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.