# NSN 5935-01-123-5349

**Thread Class:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-5349

2a and 2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
2.350 inches
Overall Height:
0.550 inches
Overall Width:
0.422 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
2.150 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and plastic phenolic single mating end

# NSN 5935-01-123-5349

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

# **Insert Material Specification:**

Mil-p-19833 military specification 1st material response single mating end and mil-m-14f military specification 2nd material response single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

40 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

# **Special Features:**

Jackscrew type-female and location-left handandjackscrew type-male and location-right hand

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.040 gold grains, troy

# **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

# Shelf Life:

N/a

# **Unit Of Measure:**

--

#### Demilitarization:

No Fiig:

#### 1020h

# Mil-std (military Standard):

Mil-g-45204 spec.