Electrical Plug Connector Body - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-123-6159

Interact Class. 3a Firead Direction: Right-hand Body Style: Hood, side opening wickamp Overall Height: 2.750 inches Overall Height: 2.750 inches Overall Height: 3.168 inches Overall Width: 1.531 inches Environmental Protection: Hunidity resistant Coule Entrance Diameter: 0.453 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Protect Couples Fire Style: Fi	Thread Class:
Prevention: Right-hand Body Style: Hood, side opening wicknapp Overall Length: 2.750 inches Overall Height: 3.780 inches Overall Vickle: 1.351 inches Environmental Protection: Humidity resistant Cable Intrance Diameter: Gaide pin/socket Shell Type: Hood, side opening Cannector Cable Strain Relief Method: Career Career Cable Intrance Interfere: Cable Interfere: Cable Interfere: Career Career <th></th>	
Right-hand Right-hand Right-hand Right-hand Side opening w/damp Overall length: 2 750 inches Overall Width: 1.531 inches Overall Vidth: 1.531 inches Environmental Protection: Humidty resistant Cable Entrance Diameter: 0.453 inches Threade Device Type: Coupling facility Mating End Quantity: 1 Polarization Method: Guide poining Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (pi): 24 Thread Size: 0.101 inches Insert Material: Plastic daily pinhalate single mating end Guide Design And Location: Shell Surface Treatment: Plastic daily pinhalate single mating end Shell Surface Treatment: Cable Clamp	
Boy Style: Hood, side opening w/damp Overall Length: 2.750 inches Overall Width: 3.168 inches Overall Width: 1.531 inches Environmental Protection: Humidty resistant Cable Entrance Diameter: 0.453 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Plarization Method: Guide pin/socket Shell Type: Hood, side opening Connector Locking Method: Cable Cartance Diameter: Cable opening Connector Locking Method: Screw Connector Locking Method: Cable clamp Thread Size: Online S Insert Material: Plastic daily pinhalate single mating end Guide pin hade single mating end Guide Sign And Location: I shape pin lethand and is hape pin right-hand at 9 colock Shell Material: Altimum alloy Shell Material Specification:	
Hod, side opening w/damp Overall Length: 2.750 Inches Overall Height: 3.168 Inches Overall Widht: 1.531 Inches Environmental Protection: Humidty resistant Cable Entrance Disconter: Overall Widh: Ox453 Inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Order Jose Guide prinsocket Stell Type: Hood, side opening Connector Locking Method: Cable Camp Threaded Device Type: Hood, side opening Connector Locking Method: Cable Camp Threaded Device Type: Iood, side opening Connector Cable Strain Relief Method: Cable Camp Thread Yer Inch (tpi): 24 Thread Size: 1.190 inches Insert Material: Plastic daily phthalate single mating end Guide pin left-hand and d shape pin right-hand at 9 colock Shell Marefae: Num	-
Overall Length:2.750 inchesOverall Height:3.168 inchesOverall Width:1.351 inchesEnvironmental Protection:Humidity resistantCable Entrance Diameter:0.453 inchesThreade Device Type:Coupling facilityMating End Quantity:1Polarization Method:Solid e peningCoupling facilityNode, side openingConnector Locking Method:SorewConnector Cable Strain Relief Method:Cable clampThreade Device Type:1Polarization Method:SorewConnector Cable Strain Relief Method:Cable clampThreade Device Type:11Polarization Method:Cable clampChread Strain Relief Method:Cable clampDistoriel Ipple:11Data Idally lphthalate single mating endCuide Loging And Location:Di shape pin left-hand and di shape pin right-hand at 9 oclockShell Metriel:Numinum alloyShell Specification:CincShell Specification:CincShell Specification:CincCincCincCincCincCincCincCincCincCincCincCincCincCincCincCincCinc	
2.750 Inches Overall Heigh: 3.168 Inches Overall With: 3.168 Inches Overall With: 1.531 Inches Environmental Protection: Hunidity resistant Cable Entrance Diameter: 0.453 Inches Threade Device Type: 0.453 Inches Threade Device Type: 0.453 Inches Threade Device Type: 0.454 Inches Mating End Quantity: 1 Polarization Method: 0.454 Polarization Method: 0.454 Polarization Method: 0.455 Polarization Polarizatio	
Overall Height:3.168 inchesOverall Width:1.531 inchesEnvironmental Protection:Humidity resistantCable Entrance Diameter:0.453 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Polarization Method:Guide pin/socketShell Type:Hodd, side openingConnector Cable Strain Relief Method:Cate dampThread Size:1.101Plattic diallyl phthalate single mating endGuide Jin/SocketSter Type:Hoed Size:Cannector Cable Strain Relief Method:Cable dampThread Size:0.190 InchesInsert Material:Platto diallyl phthalate single mating endGuide Design And Location:D shape pin left-hand and of shape pin right-hand at 9 oclockShell Type:Cable Design And Location:D shape pin left-hand and of shape pin right-hand at 9 oclockShell Type:Cable Design And Location:D shape pin left-hand at 9 oclockShell Surice Treetment:ZincStrate Treetment:ZincStrate Size:Strate Size:Strate Size:Strate Size:Strate Size:Strate Treetment:Strate Size:Strate Treetment:ZincStrate Size:Strate Size:Strate Size:Strate Size:Strate Size:Strate Size:	
3.168 inches Overall Width: 1.531 inches Environmental Protection: Humidly resistant Cable Entrance Diameter: 0.453 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Polarization Method: Guide pin/socket Shell Type: Hood, side opening Connector Locking Method: Screw Cannector Cable Strain Relief Method: Caster Thread Size: 0.190 inches Interde Size: 0.190 inches Insert Material: Plastic dialiyl phthalate single mating end Guide Design And Location: D shelp pin left-hand and shape pin night-hand at 9 oclock Shell Material: Aluminum alloy Shell Stratec Treatentent: Zinc	
Overall Width:1.531 inchesEnvironmental Protection:Humidity resistantCable Entrance Diameter:0.453 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Polarization Method:Guide pin/socketShell Type:Hood, side openingConnector Locking Method:SorewConnector Cable Strain Relief Method:24Thread Quy Per Inch (tpi):24Piterad Size:0.190 inchesInsert Material:Pidate Japin Inglich hand at 9 oclockShell Type:Shell Strain Relief Method:Connector Locking Method:Connector Cable Strain Relief Me	
1.531 inches Environmental Protection: Humidity resistant Cable Entrance Diameter: 0.453 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Polarization Method: Guide pin/socket Shell Type: Hood, side opening Connector Locking Method: Sorew Connector Cable Strain Relief Method: Cable damp Thread Size: 0.190 inches Interdistion (tpi): 24 Phera Size: 0.190 inches Insert Material: Pistic dially inthalate single mating end Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Juminum alloy Shell Strafec Treatment: Zinc	
Evrironmental Protection: Humidity resistant Cable Entrance Diameter: 0.453 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Polarization Method: Guide pin/socket Shell Type: Hod, side opening Connector Locking Method: Screw Connector Locking Method: Cable clamp Thread Size: 0.190 inches Insert Material: Plastic dially phthalate single mating end Guide pin [strift Method: Cape Plastic dially phthalate single mating end Hored Size: 0.190 inches Insert Material: Plastic dially phthalate single mating end Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum allay: Shell Surface Treatment: Zinc	
Huridity resistant Cable Entrance Diameter: 0.453 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Polarization Method: Guide pin/socket Shell Type: Hood, side opening Connector Locking Method: Sorew Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.190 inches Insert Material: Plastic dially phthalate single mating end Guide pin left-hand and dishape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatement: Zinc	
Cable Entrance Diameter: 0.453 inches Entraded Device Type: Coupling facility Mating End Quantity: 1 Polarization Method: Guide pin/socket Shell Type: Hood, side opening Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 24 Isser Material: Plastic dially Iphthalate single mating end Guide Design And Location: Plastic dially Iphthalate single mating end Schell Material: Quininum alloy Shell Surface Treatment: Zinc Material Specification:	
0.453 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Polarization Method: Guide pin/socket Shell Type: Hood, side opening Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable ctamp Thread Size: 0.190 inches Insert Material: Plastic dialtyl phthalate single mating end Guide Design And Location: p shape pin lett-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc	
Threaded Device Type: Coupling facility Mating End Quantity: 1 Polarization Method: Guide pin/socket Shell Type: Hood, side opening Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 24 Thread Size: 0.190 inches Insert Material: Plastic diallyl phthalate single mating end Guide Design And Location: 1 Plastic diallyl phthalate single mating end Screw Didde Design And Location: Plastic diallyl phthalate single mating end Murinum alloy Schell Material: Aluminum alloy Schell Surface Treatment: Zinc	
Coupling facilityMating End Quantity:1Polarization Method:Guide pin/socketShell Type:Hood, side openingConnector Locking Method:ScrewConnector Cable Strain Relief Method:Cable clampThready Qty Per Inch (tpi):24Thread Size:0.190 inchesInsert Material:Plastic diallyl phthalate single mating endGuide Design And Location:D shape pin left-hand and d shape pin right-hand at 9 oclockShell Material:Aurninum alloySchell Surface Treatment:ZincInsert Material:Aurninum alloyShell Surface Treatment:ZincInsert Material:Aurninum alloyShell Surface Treatment:ZincInsert Material Specification:	
Mating End Quantity: 1 Polarization Method: Guide pin/socket Shell Type: Hood, side opening Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 24 Thread Size: 0.190 inches Insert Material: Plastic diallyl phthalate single mating end Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Atuminum alloy Shell Surface Treatment: Zinc	
1 Polarization Method: Guide pin/socket Shell Type: Hood, side opening Connector Locking Method: Screw Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 24 Thread Size: 0.190 inches Insert Material: Plastic diallyl phthalate single mating end Guide Design And Location: 0 shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material:	
Guide pin/socketShell Type:Hood, side openingConnector Locking Method:ScrewConnector Cable Strain Relief Method:Cable clampThready Qty Per Inch (tpi):24Thread Size:0.190 inchesInsert Material:Plastic diallyl phthalate single mating endGuide Design And Location:0 shape pin left-hand and d shape pin right-hand at 9 oclockShell Material:Aluminum alloyShell Surface Treatment:ZincInsert Material Specification:	
Shell Type:Hood, side openingConnector Locking Method:ScrewConnector Cable Strain Relief Method:Cable clampThready Qty Per Inch (tpi):24Thread Size:0.190 inchesInsert Material:Plastic diallyl phthalate single mating endGuide Design And Location:0 shape pin left-hand and d shape pin right-hand at 9 oclockShell Material:Aluminum alloyShell Surface Treatment:ZincInsert Material Specification:	Polarization Method:
Shell Type:Hood, side openingConnector Locking Method:ScrewConnector Cable Strain Relief Method:Cable clampThready Qty Per Inch (tpi):24Thread Size:0.190 inchesInsert Material:Plastic diallyl phthalate single mating endGuide Design And Location:0 shape pin left-hand and d shape pin right-hand at 9 oclockShell Material:Aluminum alloyShell Surface Treatment:ZincInsert Material Specification:	Guide pin/socket
Hood, side openingConnector Locking Method:ScrewConnector Cable Strain Relief Method:Cable clampThready Qty Per Inch (tpi):24Thread Size:0.190 inchesInsert Material:Plastic diallyl phthalate single mating endGuide Design And Location:0 shape pin left-hand and d shape pin right-hand at 9 oclockShell Material:Aluminum alloyShell Surface Treatment:ZincInsert Material Specification:	
Screw Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 24 Thread Size: 0.190 inches Insert Material: Plastic diallyl phthalate single mating end Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	
Connector Cable Strain Relief Method:Cable clampThready Qty Per Inch (tpi):2424Thread Size:0.190 inchesInsert Material:Plastic diallyl phthalate single mating endGuide Design And Location:D shape pin left-hand and d shape pin right-hand at 9 oclockShell Material:Aluminum alloyShell Surface Treatment:ZincInsert Material Specification:	Connector Locking Method:
Cable clamp Thready Qty Per Inch (tpi): 24 Thread Size: 0.190 inches Insert Material: Plastic diallyl phthalate single mating end Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	Screw
Thready Qty Per Inch (tpi):2424Thread Size:0.190 inchesInsert Material:Plastic diallyl phthalate single mating endGuide Design And Location:D shape pin left-hand and d shape pin right-hand at 9 oclockShell Material:Aluminum alloyShell Surface Treatment:ZincInsert Material Specification:	Connector Cable Strain Relief Method:
24 Thread Size: 0.190 inches Insert Material: Plastic diallyl phthalate single mating end Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	Cable clamp
Thread Size:0.190 inchesInsert Material:Plastic diallyl phthalate single mating endGuide Design And Location:D shape pin left-hand and d shape pin right-hand at 9 oclockShell Material:Aluminum alloyShell Surface Treatment:ZincInsert Material Specification:	Thready Qty Per Inch (tpi):
0.190 inches Insert Material: Plastic diallyl phthalate single mating end Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	24
Insert Material: Plastic diallyl phthalate single mating end Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	Thread Size:
Plastic diallyl phthalate single mating end Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	0.190 inches
Guide Design And Location: D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	Insert Material:
D shape pin left-hand and d shape pin right-hand at 9 oclock Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	Plastic diallyl phthalate single mating end
Shell Material: Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	Guide Design And Location:
Aluminum alloy Shell Surface Treatment: Zinc Insert Material Specification:	D shape pin left-hand and d shape pin right-hand at 9 oclock
Shell Surface Treatment: Zinc Insert Material Specification:	Shell Material:
Zinc Insert Material Specification:	Aluminum alloy
Insert Material Specification:	Shell Surface Treatment:
	Zinc
Mil-m-14f, ty sdgf military specification single material response single mating end	Insert Material Specification:
	Mil-m-14f, ty sdgf military specification single material response single mating end

Electrical Plug Connector Body - Page 2 of 2



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.