Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-6178

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape

Overall Length:

4.594 inches

Overall Height:

0.938 inches

Overall Width:

0.593 inches

Distance Between Mounting Facility Centers:

4.250 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

23 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Jackscrew

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 40

Thread Size:

0.138 inches and 0.112 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end



Termina	I Туре:
Pin single	e mating end single contact grouping
Shell Ma	terial:
Aluminur	n
Shell Su	rface Treatment:
Cadmium	n
Shell Su	rface Treatment Specification:
Qq-p-416	6 federal specification single treatment response
Shell Ma	terial Specification:
Qq-a-591	I federal specification single material response
Insert Ma	aterial Specification:
Mil-m-19	833a, ty gdi-30 military specification single material response single mating end
Included	I Contact Quantity:
23 single	mating end single contact grouping
Included	I Contact Type:
Round pi	in single mating end single contact grouping
Special I	Features:
Two side	mounting holes 0.156 in. Dia
Precious	s Material And Location:
Contact s	surfaces silver and contact surfaces gold
Precious	s Material And Weight:
0.023 silv	ver grains, troy and 0.023 gold grains, troy
Precious	s Material:
Silver an	d gold
Thread S	Series Designator:
Unc and	unc
Shelf Lif	e:
N/a	
Unit Of M	Measure:
Demilita	rization:
No	
Fiig:	
A039b0	
Mil-std (military Standard):
Mil-m-19	833a spec.