Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-6257

# Thread Class:

2a

**Thread Direction:** 

Right-hand

### **Body Style:**

Straight shape, rectangular

#### **Overall Length:**

0.803 inches

#### **Overall Height:**

1.420 inches

### **Overall Width:**

2.687 inches

**Environmental Protection:** 

#### Humidity resistant

**Unthreaded Mounting Hole Diameter:** 

### 0.149 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.375 inches

### Threaded Device Type:

Coupling facility

## Mating End Quantity:

1

# **Contact Removability:**

Removable single mating end single contact grouping

# Contact Maximum Current Rating In Amps:

8.5 single mating end single contact grouping

# Contact Maximum Ac Voltage Rating In Volts:

2000.0 single mating end single contact grouping

# Polarization Method:

Guide pin/socket

# **Connector Locking Method:**

Screw

# Thready Qty Per Inch (tpi):

24

### Thread Size:

0.190 inches

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Wire wrap single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

#### **Guide Design And Location:**

D shape socket right-hand at 10 oclock

#### **Insert Material Specification:**

Mil-m-14f, ty sdgf military specification single material response single mating end

#### **Included Contact Quantity:**

120 single mating end single contact grouping

#### **Included Contact Type:**

Hermaphrodite single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.120 gold grains, troy

# **Precious Material:**

Gold

### **Thread Series Designator:**

Unc

# Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-m-14f spec.