NSN 5935-01-123-6259

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-6259

| Thread Class: |
|---|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, rectangular |
| Overall Length: |
| 0.803 inches |
| Overall Height: |
| 0.875 inches |
| Overall Width: |
| 2.592 inches |
| Environmental Protection: |
| Moisture resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.136 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.468 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 2.280 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 8.5 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Screw |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.125 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-123-6259

Electrical Receptacle Connector - Page 2 of 2



| Insert Material: |
|---|
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Contact Material Specification: |
| Qq-b-750, comp a federal specification single material response single mating end single contact grouping |
| Guide Design And Location: |
| D shape socket left-hand at 9 oclock and d shape socket right-hand at 9 oclock |
| Insert Material Specification: |
| Mil-m-14, ty sdg-f military specification single material response single mating end |
| Included Contact Quantity: |
| 56 single mating end single contact grouping |
| Included Contact Type: |
| Hermaphrodite single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.056 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.