NSN 5935-01-123-6436

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-6436

| Body Style: |
|---|
| Straight type |
| Overall Length: |
| 4.900 inches |
| Overall Height: |
| 0.755 inches |
| Overall Width: |
| 0.400 inches |
| Environmental Protection: |
| Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| Distance Between Mounting Facility Centers: |
| 4.650 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 3 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Friction |
| Operating Tempurature Rating: |
| Between -65.0 degrees celsius and 125.0 degrees celsius |
| Terminal Location: |
| Back single mating end single contact grouping |

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

NSN 5935-01-123-6436

Electrical Receptacle Connector - Page 2 of 2



Guide Design And Location:

D shape pin left-hand at 12 oclock and d shape pin right-hand at 12 oclock

Insert Material Specification:

Mil-m-14, ty gdi-30 or ty sdg-f military specification single material response single mating end

Included Contact Quantity:

122 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.122 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.