NSN 5935-01-123-6443

Body Style:

Flush flange mounting

Overall Length: 2.078 inches

2.062 inches

1.250 inches

Bushing Diameter:

Mounting Hole Circle Radius:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-6443

Overall Diameter:			
2.875 inches			
Environmental Protection:			
Corrosion resistant			
Unthreaded Mounting Hole Diameter:			
0.187 inches			
Mating End Quantity:			
1			
Contact Position Arrangement Style:			
3 single mating end			
Contact Removability:			
Nonremovable single mating end all contact groupings			
Contact Maximum Current Rating In Amps:			
30.0 single mating end all contact groupings			
Contact Maximum Ac Voltage Rating In Volts:			
277.0 single mating end all contact groupings			
Polarization Method:			
Contact			
Shell Type:			
Shell Type: Solid			
Solid			
Solid Connector Locking Method:			
Solid Connector Locking Method: Contact twistlock			
Solid Connector Locking Method: Contact twistlock Terminal Location:			
Solid Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings			
Solid Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings Contact Material:			
Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings			
Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Insert Material:			
Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Insert Material: Plastic polyamide single mating end			
Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Insert Material: Plastic polyamide single mating end Terminal Type:			
Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Insert Material: Plastic polyamide single mating end Terminal Type: Screw single mating end all contact groupings			
Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Insert Material: Plastic polyamide single mating end Terminal Type: Screw single mating end all contact groupings Included Contact Quantity: 2 single mating end 2nd contact grouping Included Contact Type:			
Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Insert Material: Plastic polyamide single mating end Terminal Type: Screw single mating end all contact groupings Included Contact Quantity: 2 single mating end 2nd contact grouping			
Connector Locking Method: Contact twistlock Terminal Location: Side single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Insert Material: Plastic polyamide single mating end Terminal Type: Screw single mating end all contact groupings Included Contact Quantity: 2 single mating end 2nd contact grouping Included Contact Type:			

NSN 5935-01-123-6443

Electrical Receptacle Connector - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0