## NSN 5935-01-123-6456

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-6456

Thread Class:
2b and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
1.185 inches
Overall Height:
0.500 inches
Overall Width:
0.305 inches
Environmental Protection:
Moisture resistant and salt water resistant and thermal shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
0.965 inches
Threaded Device Type:
Coupling facility and mounting stud
Moting End Quantity
Mating End Quantity:
1
1
1 Contact Position Arrangement Style:
1 Contact Position Arrangement Style: 25 single mating end
Contact Position Arrangement Style: 25 single mating end Contact Removability:
Contact Position Arrangement Style: 25 single mating end Contact Removability: Nonremovable single mating end single contact grouping
Contact Position Arrangement Style: 25 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method:
Contact Position Arrangement Style: 25 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Jackscrew
Contact Position Arrangement Style: 25 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Jackscrew Shell Type:
Contact Position Arrangement Style: 25 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid
Contact Position Arrangement Style: 25 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method:
Contact Position Arrangement Style: 25 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket
Contact Position Arrangement Style: 25 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi):
Contact Position Arrangement Style:  25 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping  Polarization Method:  Jackscrew  Shell Type:  Solid  Connector Locking Method:  Jackscrew-socket  Thready Qty Per Inch (tpi):  56 and 56 and 56
Contact Position Arrangement Style:  25 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping  Polarization Method:  Jackscrew  Shell Type:  Solid  Connector Locking Method:  Jackscrew-socket  Thready Qty Per Inch (tpi):  56 and 56 and 56  Thread Size:

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Glass single mating end and plastic diallyl phthalate single mating end

## NSN 5935-01-123-6456

Electrical Receptacle Connector - Page 2 of 2



Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Insert Material Specification:** 

Mil-m-14, type sdgf military specification single material response single mating end

**Unable To Decode:** 

Unable to decode and unable to decode

**Included Contact Quantity:** 

25 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Special Features:** 

24 in. No. 26 awg wire leads

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.025 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc and unc

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.