Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-123-7867



Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle, shape, internal coupling

Overall Length:

1.000 inches

Overall Height:

0.550 inches

Overall Diameter:

0.250 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Rf single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Shrinkable tubing

Thready Qty Per Inch (tpi):

36

Thread Size:

0.190 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c or d military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

NSN 5935-01-123-7867 Electrical Plug Connector - Page 2 of 2



| Terminal [•] Solder we | Il single mating end single contact grouping |
|------------------------------------|--|
| | |
| | faterial Specification: |
| | federal specification single material response single mating end single contact grouping |
| Shell Mate Stainless s | |
| | face Treatment: |
| Passivate | ace meatment. |
| | face Treatment Specification: |
| | ederal specification single treatment response |
| | erial Specification: |
| | type 302 or type 305 federal specification single material response |
| • | terial Specification: |
| | 88 military specification single material response single mating end |
| | Contact Quantity: |
| | ating end single contact grouping |
| - | Contact Type: |
| | n single mating end single contact grouping |
| - | Material And Location: |
| | urface gold |
| | Material And Weight: |
| 0.005 gold | l grains, troy |
| Precious | Material: |
| Gold | |
| Thread Se | eries Designator: |
| Uns | |
| Shelf Life | : |
| N/a | |
| Unit Of M | easure: |
| | |
| Demilitari | zation: |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (m | nilitary Standard): |
| Mil-g-4520 |)4 spec. |