NSN 5935-01-123-8120

Aluminum alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-8120

Body Style:
Straight shape, flush mount
Overall Length:
1.061 inches
Overall Height:
3.075 inches
Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.783 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
0.060 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
67 2nd mating end
Contact Removability:
Removable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
7.5 2nd mating end 2nd contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings and silver all mating ends all contact groupings
Insert Material:
Plastic diallyl phthalate all mating ends
Terminal Type:
Crimp all mating ends all contact groupings
Guide Design And Location:
Hexagon shape female post left-hand at 6 oclock and hexagon shape female post center at 6 oclock and hexagon shape female post
right-hand at 6 oclock
Shell Material:

NSN 5935-01-123-8120

Mil-std (military Standard):

Mil-p-19833 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-p-19833, ty gdi-30f military specification single material response all mating ends
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.097 gold grains, troy and 0.097 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0