## NSN 5935-01-123-8521

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-8521 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.780 inches **Overall Height:** 1.343 inches **Overall Width:** 1.343 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.490 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.188 inches **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel **Shell Surface Treatment Specification:** 

Mil-c-26074 cl 3 or 4, grade b military specification single treatment response

## **Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5935-01-123-8521

Receptacle Dummy Connector - Page 2 of 2



Thread Series Designator:
Unef
Specification Data:
81349-mil-c-83723/61 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-c-26074 spec.