

View Online at <https://aerobasegroup.com/nsn/5935-01-123-8522>

**Overall Length:**

Between 0.508 inches and 0.571 inches

**Overall Height:**

0.828 inches

**Overall Width:**

0.828 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.594 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.594 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.462 inches and 0.493 inches

**Mating End Quantity:**

1

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-c-26074 cl 3, grade b military specification single treatment response

**Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

96906-ms3115 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-c-26074 spec.