Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-8528

## Thread Class:

2a

**Thread Direction:** 

Right-hand

#### **Body Style:**

Straight shape, external coupling

#### **Overall Length:**

2.128 inches

**Overall Height:** 

1.562 inches

**Overall Width:** 

1.562 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

0.128 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

## Distance From Mounting Shoulder To Front Face:

0.930 inches

#### Threaded Device Type:

Back shell

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

21-35 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0

#### Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Thread Length:** 

0.219 inches

## Thready Qty Per Inch (tpi):

# NSN 5935-01-123-8528

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.188 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
79 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts72 through 79 ground, contacts 56, 57, 70 and 71 insulated, contacts 52, 53, 68 and 69 filter 375 pf, remaining 63 contacts 750 pf
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.079 gold grains, troy and 0.079 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0