

View Online at <https://aerobasegroup.com/nsn/5935-01-123-8531>

Thread Class:

2b and 2a

Thread Direction:

Right-hand

Body Style:

Straight type

Overall Length:

3.850 inches

Overall Height:

0.657 inches

Overall Width:

0.250 inches

Environmental Protection:

Moisture resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

3.600 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder stud single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty gdi-30f or ty sdg-f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

60 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-female and location-left hand and jackscrew type-male and location-right hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.060 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.