NSN 5935-01-123-8533

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-8533

| view Online at https://derobasegroup.com/nsn/0000-01-120-0000 |
|---|
| Body Style: |
| Straight shape |
| Overall Length: |
| 5.130 inches |
| Overall Height: |
| 0.829 inches |
| Overall Width: |
| 0.400 inches |
| Distance Between Mounting Facility Centers: |
| 4.750 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of independent contacts inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Polarization Method: |
| Contact to contact polarizing keys |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Included Contact Quantity: |
| 80 single mating end single contact grouping |
| Included Contact Type: |
| Hermaphrodite single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.080 gold grains, troy |

Gold

Precious Material:

NSN 5935-01-123-8533

Electrical Receptacle Connector - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0