NSN 5935-01-123-8539

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-123-8539 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.590 inches **Overall Diameter:** 2.078 inches **Environmental Protection:** Moisture resistant **Distance From Mounting Shoulder To Front Face:** 0.772 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 120.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 226.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi):

Thread Size:

18 and 18

1.312 inches and 1.500 inches

NSN 5935-01-123-8539

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416 federal specification all treatment responses
Shell Material Specification:
Qq-a-367 federal specification single material response
Included Contact Quantity:
55 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0