

View Online at <https://aerobasegroup.com/nsn/5935-01-123-9910>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

1.783 inches

**Overall Height:**

0.658 inches

**Overall Width:**

0.330 inches

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Distance Between Mounting Facility Centers:**

1.533 inches

**Board Accommodated Length:**

1.220 inches single board

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1800.0 single mating end single contact grouping

**Polarization Method:**

Contact

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 type 2 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14 color green military specification single material response single mating end

**Included Contact Quantity:**

12 single mating end single contact grouping

**Included Contact Type:**

Bifurcated accordian leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.012 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.