

View Online at <https://aerobasegroup.com/nsn/5935-01-124-7229>

Unthreaded Mounting Hole Diameter:

Between 0.066 inches and 0.071 inches

Mating End Quantity:

1

Contact Maximum Dc Voltage Rating In Volts:

50.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

End Application:

Alq137/f111

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Nickel single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Qq-n-290, class 2 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204, type ii military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-w-321 federal specification single material response single mating end single contact grouping or qq-b-613 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 12 o'clock

Shell Material:

Aluminum alloy 6063 or aluminum alloy 6061

Shell Material Specification:

Qq-a-200/9 federal specification 1st material response and qq-a-200/18 federal specification 2nd material response

Insert Material Specification:

Mil-m-20693 military specification single material response single mating end

Included Contact Quantity:

30 single mating end single contact grouping

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.