NSN 5935-01-125-0952

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-125-0952 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.232 inches **Overall Height:** 1.234 inches **Overall Width:** 1.234 inches **Environmental Protection:** Corrosion resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** 0.431 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 165.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 20 **Thread Size:** 1.000 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-125-0952

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade e federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

19 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.019 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.